

4U102 Hybrid Storage Platform

♦ Features

- Up to 102 Ultrastar® He 12 HDDs (SAS or SATA)
- Hybrid support with up to 24 SSDs (SAS or SATA) for a data acceleration tier
- Up to 1.2PB of raw storage in 4U
- Choose dual-port SAS for high availability or single-port SATA for low cost
- 4 rack units, 1047mm depth
- Up to 12 x 12Gb/s SAS3 host connections
- Patented IsoVibe technology ensures maximum performance even in heavy workloads
- Enterprise-grade redundant and hotswappable PSUs, IO Modules and fans
- Improved cooling from innovative, patented ArcticFlow™ technology
- Rack-mounted top cover for quick and easy service



102-Bay Hybrid Storage Platform Overview The Next Generation Hybrid Platform for Software-Defined Storage



Designed for High Density and Flexibility

The 4U102 Hybrid Storage Platform is a key element of next-generation disaggregated storage and software-defined storage (SDS) systems, delivering high density and the flexibility to balance performance with cost. The 4U102 Platform provides up to 1.2PB¹ of raw storage in a compact and efficient form factor. HGST HelioSeal® drives ensure cool running, quiet operation and high reliability. A high performance data tier can be set up for demanding applications by using SSDs in up to 24 of the drive slots.

Building on 50+ years of Storage Design Experience
Conventional dense disk shelves frequently suffer from performance
degradation due to induced vibration from adjacent drives.
Traditional platforms also have cooling challenges as the cooling
air passes over successive rows of drives, losing effectiveness as it
gets heated up along the airflow path. Developing storage devices
and platforms side-by-side, we address these challenges through
vertical innovation, a set of technologies developed based on a
holistic view of devices, platform, and their interactions. The first
two of these patented technologies are IsoVibe™ and ArcticFlow™.
IsoVibe reduces vibration-induced performance degradation, while
ArcticFlow overcomes the cooling issues by introducing cool air into
the middle of the platform. Both these technologies contribute to
long-term reliability, enabling our five-year limited warranty on the
entire platform.

Designed for the Enterprise and the Cloud:

This new platform addresses the demanding storage needs of large enterprise customers, storage OEMs, cloud service providers and resellers/integrators that require dense, shared HDD or hybrid storage. The 4U102 Hybrid Storage Platform provides the flexibility to specify the HDD and SSD combinations to balance capacity, performance and cost.



4U102 Hybrid Storage Platform



IsoVibe Patented Vibration Isolation Technology

Precise cuts in the baseboard provide a suspension for the drives in the chassis, isolating them from transmitted vibration. The result is that consistent performance is maintained, even when all the drives are working hard.



Arctic Flow Patented Thermal Zone Cooling technology

By introducing cool air into the center of the chassis, drives operate at lower and more consistent temperatures than conventional systems. This results in lower fan speeds, reduced vibration, lower power consumption, quieter operation and ultimately higher reliability.

Specifications

Max. Drives	 102 x 3.5" drive bays Up to 24 can be SAS or SATA SSD
Drive Interface	12Gb/s SAS 6Gb/s SATA
Available Drive Capacities	HDD up to 12TB SSD up to 6.4TB
Host Interface	 Dual redundant I/O Modules (IOM), 6 Mini-SAS HD ports per IOM
Weight	 4U102 w/o drives: 31.8kg (70lbs) 4U102 w/ 102 HDDs: 118.8kg (262lbs)
LED Indicators	Front/Rear: Power, ID, Fault Drive: Activity, Fault
Physical Dimensions	 Height: 175mm (6.89") Width: 447mm (17.61") Depth: 1047mm (41.25")
Management	SCSI Enclosure Services Redfish (out of band, via RJ45)
Power	 Dual 1600W, 80+ Platinum 200-240V AC input, auto ranging, 50-60Hz
Cooling	 4 main enclosure fans, front-to-rear system cooling with zero-loss backflow prevention 2 IO module fans Dual PSUs with built-in fans Fan speed tuning via system management
Environmental	 Operating Temperature: 5 to 40°C Non-op Temperature: -40 to 60°C Humidity: 5 to 85% relative humidity Operating Altitude: 40°C @ 3,000ft Sound Power: < 7.2Bels @ 23±2°C
Serviceability	Cable-free hot-swappable IOM, power supply, fans and drives

Contact

Sales Inquiries
North America: salesNA@hgst.com
Europe/Middle East/Africa (EMEA): salesEMEA@hgst.com
Asia/Pacific: salesAP@hgst.com
Japan: salesJP@hgst.com

Information & Technical Support http://www.hgst.com/support/platforms-support Partner Program Inquiries channelpartners@hgst.com

Western Digital Corporation 5601 Great Oaks Parkway

San Jose, CA 95119 USA

© 2017 Western Digital Corporation or its affiliates. All rights reserved. Western Digital, the HGST logo, ArcticFlow, Helioseal, IsoVibe, and Ultrastar are registered trademarks or trademarks of Western Digital Corporation or its affiliates in the US and/or other countries. All other marks are the property of their respective owners.